

**Product Features**

BNC Male to RG-316 cable using RG Type Flex 12 Coax, 0.098 inches long, and Operating to 0.1 GHz.



**Electrical Specification: T<sub>Ambient</sub> = 25° C**

| Parameter               | Frequency Range | Units  | Min | Typical | Max  | Notes |
|-------------------------|-----------------|--------|-----|---------|------|-------|
| Frequency Range         |                 | GHz    | DC  |         | 3.0  |       |
| VSWR                    | DC to 0.1       | 1:     |     |         | 1.2  |       |
|                         | 0.1 to 0.4      |        |     |         | 1.25 |       |
|                         | 0.4 to 1.0      |        |     |         | 1.3  |       |
|                         | 1.0 to 2.4      |        |     |         | 1.35 |       |
| Insertion Loss          | DC to 0.1       | dB/ft. |     |         | 0.09 |       |
|                         | 0.1 to 0.4      |        |     |         | 0.18 |       |
|                         | 0.4 to 1.0      |        |     |         | 0.31 |       |
|                         | 1.0 to 2.4      |        |     |         | 0.49 |       |
| Velocity Of Propagation |                 | %      |     | 69.5    |      |       |

**Mechanical And Environmental Specifications:**

| Parameter                | Description                        | Notes |
|--------------------------|------------------------------------|-------|
| Connector 1              | MMCX Plug Right Angle              |       |
| Connector 1 Coupling Nut | None                               |       |
| Connector 1 Body         | Gold Plated Brass                  |       |
| Connector 1 Contact      | Gold Plated Brass                  |       |
| Connector 2              | BNC Male                           |       |
| Connector 2 Coupling Nut | Tin-Zinc-Copper-Alloy Plated Brass |       |
| Connector 2 Body         | Tin-Zinc-Copper-Alloy Plated Brass |       |
| Connector 2 Contact      | Gold Plated Brass                  |       |
| Coax Cable               | RG Type Flex                       |       |
| Cable Type               | RG-316                             |       |
| Cable Inner Conductor    | 7/.0067 SPCW                       |       |
| Dielectric               | PTFE                               |       |
| Shield                   | 1. SPC Braid                       |       |
| Jacket                   | FEP                                |       |
| Coax Diameter            | 0.098                              |       |
| Minimum Bend Radius      | 0.5                                |       |
| Length                   | 12.0                               |       |

# P1-BNCP/MMCXPRA-RG316-12

MMCX Plug Right Angle to BNC Male cable using RG-316 RG Type Flex Coax, 12 inches long, and Operating to 3 GHz.

| Parameter             | Description       | Notes |
|-----------------------|-------------------|-------|
| Operating Temperature | -55.0 to 200.0 °C |       |
| RoHS Compliance       | Yes               |       |

## Product Notes