

P1-BNCP/SMBP-RD316-36

BNC Male to SMB Plug cable using RD316 Double-Shielded Flex Coax, 36 inch, frequency to 3 GHz.

Product Features

P1-BNCP/SMBP-RD316-36 is a cable that is part of P1dB's RG series flex cable assemblies. It is a 36 inch BNC Male to SMB Plug cable assembly that utilizes RD316 Double-Shielded RG Type Flex coax, which is 0.114 inches in diameter. This Double-Shielded RG Type Flex cable operates to 3 GHz with a max VSWR of 1.35:1. P1dB's Double-Shielded RG Type Flex cable assemblies are general purpose commercial grade cables that meet dimensional and electrical specifications of QPL cables. Double-Shielded RG Type Flex cables can operate up to 6 GHz, depending on the installed connectors. The advantage of RG type commercial cables over QPL cables is their lower cost, since they do not go through the stringent environmental, mechanical and certification testing required for military grade, QPL equivalents.



Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		3.0	
VSWR	DC to 0.4	1:			1.2	
	0.4 to 1.0				1.25	
	1.0 to 2.4				1.3	
Insertion Loss	DC to 0.4	dB/ft.			0.18	
	0.4 to 1.0				0.31	
	1.0 to 2.4				0.49	
Velocity Of Propagation		%		69.5		

Electrical Specification: T Ambient = 25° C

Mechanical And Environmental Specifications:

Parameter	Description	Notes	
Connector 1	BNC Male		
Connector 1 Coupling Nut	Tin-Zinc-Copper-Alloy Plated Brass		
Connector 1 Body	Tin-Zinc-Copper-Alloy Plated Brass		
Connector 1 Contact	Gold Plated Brass		
Connector 2	SMB Plug		
Connector 2 Coupling Nut	None		
Connector 2 Body	Gold Plated Brass		
Connector 2 Contact	Gold Plated Brass		
Coax Cable	Double-Shielded RG Type Flex		
Cable Type	RD316		
Cable Inner Conductor	7/.0067 SPCW		
Dielectric	PTFE		
Shield	1. SPC Braid		
	2. SPC Braid		
Jacket	FEP		
Coax Diameter	0.114		

188 Martinvale Lane, San Jose, CA 95119



P1-BNCP/SMBP-RD316-36

BNC Male to SMB Plug cable using RD316 Double-Shielded Flex Coax, 36 inch, frequency to 3 GHz.

Parameter	Description	Notes
Minimum Bend Radius	0.6	
Length	36.0	
Operating Temprature	-55.0 to 125.0 °C	
RoHS Compliance	Yes	

Product Notes