

P1-SMAP/SMAP-141CC-17

SMA Male to SMA Male cable assembly using 141CC Conformable Coax, 17 inch, frequency to 26.5 GHz.

Product Features

P1-SMAP/SMAP-141CC-17 is an RF Cable that is part of P1dB's YouForm $^{\text{TM}}$ conformable cable assembly series. It is a 17 inch SMA Male to SMA Male Conformable cable assembly that utilizes 141CC conformable coax with a diameter of 0.141 inches. The RF cable assembly operates to 26.5 GHz with a max VSWR of 1.35:1.

YouForm[™] cables are conformable and jacketed conformable versions 085 and 141 semi-rigid coax cables and meet RG402 and RG405 dimensional and electrical specifications. YouForm[™] cable assemblies can operate up to 18 GHz, depending on the configuration. The advantage of YouForm[™] conformable cables over semi-rigid are their ability to be formed by hand multiple times, while semi-rigid cables can be formed only once with special bending tools.



Electrical Specification: T_{Ambient} = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		26.5	
VSWR	DC to 1.0	1:			1.25	
	1.0 to 5.0				1.3	
	5.0 to 10.0				1.32	
	10.0 to 26.5				1.35	
Insertion Loss	DC to 1.0	dB/ft.			0.12	
	1.0 to 5.0				0.31	
	5.0 to 10.0				0.45	
	10.0 to 26.5				0.65	
Velocity Of Propagation		%		70.0		

Mechanical And Environmental Specifications:

Parameter	Description	Notes	
Connector 1	SMA Male		
Connector 1 Coupling Nut	Passivated Stainless Steel		
Connector 1 Body	Gold Plated Brass		
Connector 1 Contact	Gold Plated Brass		
Connector 2	SMA Male		
Connector 2 Coupling Nut	Passivated Stainless Steel		
Connector 2 Body	Gold Plated Brass		
Connector 2 Contact	Gold Plated Brass		
Coax Cable	Conformable		
Cable Type	141CC		
Cable Inner Conductor	SPCW		
Dielectric	PTFE		
Shield	1. Tinned Cu/Sn Braid		
Jacket	FEP		

P1dB, Inc.

188 Martinvale Lane, San Jose, CA 95119

+1(408)613-4857



P1-SMAP/SMAP-141CC-17

SMA Male to SMA Male cable assembly using 141CC Conformable Coax, 17 inch, frequency to 26.5 GHz.

Parameter	Description	Notes
Coax Diameter	0.141	
Minimum Bend Radius	0.38	
Length	17.0	
Operating Temprature	-85.0 to 165 °C	
RoHS Compliance	Yes	

Product Notes