P1AD-18F24M

RF Adapter, 1.85mm Female to 2.4mm Male, VSWR 1.25 max up to 50 GHz

Product Features

P1AD-18F24M is a 50 Ohm high frequency adapter, 1.8mm female to 2.4mm male, operating to 50 GHz. Maximum VSWR is 1.25. Material is passivated stainless steel.

P1dB offers a large selection of standard and precision 50 Ohm RF adapters for lab, aerospace, industrial and commercial applications. In-series and between series options include 1.85mm, 2.4mm, 2.92mm, 3.5mm, SMA, Type N, TNC and BNC.



Electrical Specification: $T_{Ambient}$ = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Impedance				50.0		

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	1.85mm Female	
Connector 2	2.4mm Male	
Orientation	Straight	
Mount Type	None	
RoHS Compliance	Yes	


Drawing

P1dB, Inc. 188 Martinvale Lane, San Jose, CA 95119 +1(408)613-4857

sales@p1dB.com

P1AD-18F24M

RF Adapter, 1.85mm Female to 2.4mm Male, VSWR 1.25 max up to 50 GHz



Graph

Parts	Material	Plating (Micro-inch)
Gasket	Silicone	
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator	PPO	
Body	Stainless Steel	Passivated
Coupling Nut	Stainless Steel	Passivated

Product Notes

P1dB, Inc. 188 Martinvale Lane, San Jose, CA 95119 +1(408)613-4857

sales@p1dB.com