# P1AD-24F29F

RF Adapter, 2.4mm Female to 2.92mm Female, VSWR 1.25 max to 40 GHz

### Product Features

P1dB's P1AD-24F29F is a straight 2.4mm Female to 2.92mm Female adapter that operates to 40 GHz with a maximum VSWR of 1.25:1. It has a Stainless Steel body and meets operating temperatures from -85 to 125 degrees Celcius.

P1dB offers a large selection of standard and precision 50 Ohm RF adapters for lab, aerospace, industrial and commercial applications. In-series and between series options include 1.85mm, 2.4mm, 2.92mm, 3.5mm, SMA, Type N, TNC and BNC.




### Electrical Specification: $T_{Ambient}$ = 25° C

| Parameter | Frequency Range | Units | Min | Typical | Max | Notes |
|---|---|---|---|---|---|---|
| Impedance | | | | 50.0 | | |

### Mechanical And Environmental Specifications:

| Parameter | Description | Notes |
|---|---|---|
| Connector 1 | 2.4mm Female | |
| Connector 2 | 2.92mm Female | |
| Orientation | Straight | |
| Mount Type | None | |
| RoHS Compliance | Yes | |

### Product Notes

**P1dB, Inc.** 188 Martinvale Lane, San Jose, CA 95119 +1(408)613-4857

sales@p1dB.com