P1AD-SAFMMXP

Adapter, SMA female to MMCX plug (male) Gold plated brass body, VSWR 1.3 max to 6 GHz.

Product Features

P1AD-SAFMMXP is a 50 Ohm RF adapter, SMA female to MMCX plug (male). Operating to 6 GHz with a max VSWR of 1.30. Adapter body is gold plated brass.



Electrical Specification: $T_{Ambient}$ = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		6.0	

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	SMA Female	
Connector 1 Body	Gold Plated Brass	
Connector 1 Contact	Gold Plated Beryllium Copper	
Connector 2	MMCX Plug	
Operating Temprature	-40.0 to 85.0 °C	
RoHS Compliance	Yes	


Drawing

P1dB, Inc. 188 Martinvale Lane, San Jose, CA 95119 +1(408)613-4857

sales@p1dB.com

P1AD-SAFMMXP

Adapter, SMA female to MMCX plug (male) Gold plated brass body, VSWR 1.3 max to 6 GHz.



Product Notes

P1dB, Inc. 188 Martinvale Lane, San Jose, CA 95119 +1(408)613-4857

sales@p1dB.com