


P1CA-29M29M-ST085-3

2.92mm Male to 2.92mm Male cable assembly using ST085 Tight-Flex, Triple Shielded Coax, 3 inch

Product Features

P1CA-29M29M-ST085-3 is an RF Cable that is part of P1dB Tight-Flex™ cable assembly series. With a minimum bend radius of 0.2 inch, the cable allows bends at the connector end eliminating the need for a right angle connector. It is a 3 inch 2.92mm Male to 2.92mm Male cable assembly that utilizes ST085 Tight-Flex, Triple Shielded coax, which is 0.104 inches in diameter. The Tight-Flex™ cable assembly operates to 40 GHz with a max VSWR of 1.35:1.

Tight-Flex™ cable assemblies are a flexible version of RG405 semi-rigid and 085 conformable coax cables that meet RG405 dimensional and electrical specifications. Tight-Flex™ cable assemblies can operate up to 40 GHz, depending on the installed connectors. The advantage of Tight-Flex™ cables over other 085 flex cables are their triple shielding that add additional RF stability even during tight bends.



Electrical Specification: T_{Ambient} = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		40.0	

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	2.92mm Male	
Connector 2	2.92mm Male	
Coax Cable	Tight-Flex, Triple Shielded	
Cable Type	ST085	
Coax Diameter	0.104	
Length	2.0	
RoHS Compliance	Yes	

Product Notes

P1CA-29M29M-ST085-3

2.92mm Male to 2.92mm Male cable assembly using ST085 Tight-Flex, Triple Shielded
Coax, 3 inch

