


**Product Features**

P1CA-29M29M-ST085-20 is an RF Cable that is part of P1dB's Tight-Flex™ cable assembly series. With a minimum bend radius of 0.2 inch, the cable allows bends at the connector end eliminating the need for a right angle connector. It is a 20 inch 2.92mm Male to 2.92mm Male cable assembly that utilizes ST085 Tight-Flex, Triple Shielded coax, which is 0.104 inches in diameter. The Tight-Flex™ cable assembly operates to 40 GHz with a max VSWR of 1.35:1.


Tight-Flex™ cable assemblies are a flexible version of RG405 semi-rigid and 085 conformable coax cables that meet RG405 dimensional and electrical specifications. Tight-Flex™ cable assemblies can operate up to 40 GHz, depending on the installed connectors. The advantage of Tight-Flex™ cables over other 085 flex cables are their triple shielding that add additional RF stability even during tight bends.



**Mechanical And Environmental Specifications:**

Parameter	Description	Notes
Connector 1	2.92mm Male	
Connector 2	2.92mm Male	
Coax Cable	Tight-Flex, Triple Shielded	
Cable Type	ST085	
Coax Diameter	0.104	
Length	20	
RoHS Compliance	Yes	

**Drawing**



**Graph**

DIMENSIONS			
Center Conductor Diameter			
(inch)			0.0201
(mm)			0.51
Dielectric Diameter			
(inch)			0.0641
(mm)			1.63
Diameter Over Inner Foil			
(inch)			0.0708
(mm)			1.80
Diameter Over Outer Foil			
(inch)			0.0748
(mm)			1.90
Diameter over Braid			
(inch)			0.0885
(mm)			2.25
Jacket Diameter			
(inch)			0.104
(mm)			2.64
MATERIAL SPECIFICATIONS			
Jacket	FEP(BLUE)		
Braid	Round Silver Plated Copper		
Outer Foil	Aluminium Tape		
Inner Foil	Silver Plated Copper Tape		
Dielectric	Solid PTFE		
Center Conductor	Solid SPCW		
ELECTRICAL CHARACTERISTICS			
Impedance	50±2		
Capacitance (Nominal)			
(pF/ft)	29.4		
(pF/m)	96.4		
Velocity of Propagation (%)	70		
Cutt Off Frequency (GHz)	63		
Shielding Effectiveness	> -110dB		
Max. Attenuation Max Power (Watts)	Attenuation		Power
	dB/100Ft	dB/100M	
400MHz	14	45.9	240
1GHz	23	75.4	160
3GHz	39	128	80
5GHz	52	170.6	57
10GHz	80	262.4	44
18GHz	110	361	33
25GHz	131	430	29
30GHz	146	479	26
35GHz	160	525	23
40GHz	173	567	22
45GHz	183	600	20
50GHz	195	640	18

**Product Notes**