

## P1CA-NMNM-195TM-60

Cable Assembly, N Male to N Male, 195TM Phase Stable Coax, 60 inches. DC to 18 Ghz. Limited to stock on hand.

#### **Product Features**

P1CA-NMNM-195TM-60 is a 50 Ohm flexible test cable, 0.195 inch outer diameter, operating to 18 GHz. This assembly is a low loss, phase stable cable with precision stainless steel N male to N male connectors, 60 inches long. Triple shield design for high RF isolation and microporous dielectric for low insertion loss. Enhanced cable-to-connector boot extends the operating life of this rugged test cable.

Typical insertion loss at 18 Ghz is 0.68 dB/ ft. Velocity of propagation is 70%. Maximum VSWR is 1.30 to 18 GHz.

Phase stability vs. flexure is +/- 2 degrees to 18 GHz.



#### Electrical Specification: T Ambient = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		18.0	

#### **Mechanical And Environmental Specifications:**

Parameter	Description	Notes	
Connector 1	N Male		
Connector 2	N Male		
Coax Cable	Test Grade		
Cable Type	195TM		
Coax Diameter	0.195		
Length	60.0		
RoHS Compliance	Yes		

#### Drawing



# P1CA-NMNM-195TM-60

Cable Assembly, N Male to N Male, 195TM Phase Stable Coax, 60 inches. DC to 18 Ghz. Limited to stock on hand.

### **Mechanical Specification**

Parameter	Description	Notes
Connector Type	SMA (18 GHz or 26.5 GHz), N, TNC, BNC	Male and Female
Connector Body Material and Plating	Passivated Stainless Steel	
Connector Contact Material and Plating	Gold Plated Beryllium Copper	
Connector Retention	170 lbs.	
Mating Cycles	>5,000	SMA, N and TNC
Cable Inner Conductor	Silver Plated Solid Copper	
Dielectric	PTFE	
Shield	1. Silver Plated Copper Flat Ribbon Braid	
	2. Aluminum Polyimide Tape	
	<ol><li>Silver Plated Copper Round Braid</li></ol>	
Jacket	Translucent Blue FEP	
Coax Diameter	.195 inch	
Minimum Bend Radius	1 inch	
Flexure Cycles	>50,000	

### **Product Notes**

Minimum bend radius is 1.0 inch.

Operating temperature is -55 to +105 degrees C.