


**Product Features**

P1CA-SAFPT-020SR-6 is an RF Test Probe that is part of P1dB's semi-rigid, conformable, jacketed conformable and flexible Pigtail assembly series. It is a 6 inch SMA Female to a Pigtail Semi-Rigid cable assembly that utilizes 020SR conformable coax with a diameter of 0.02 inches. The Pigtail cable assembly operates to 6 GHz and is a popular solution for in-circuit RF probe testing.




**Electrical Specification: T<sub>Ambient</sub> = 25° C**

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		6.0	
Insertion Loss	DC to 1.0	dB/ft.			0.73	
	1.0 to 3.0				1.22	
	3.0 to 5.0				1.66	
Velocity Of Propagation		%		70.0		

**Mechanical And Environmental Specifications:**

Parameter	Description	Notes
Connector 1	SMA Female	
Connector 1 Coupling Nut	None	
Connector 1 Body	Gold Plated Brass	
Connector 1 Contact	Gold Plated Beryllium Copper	
Connector 2	Pigtail - No Connector	
Coax Cable	Semi-Rigid	
Cable Type	020SR	
Cable Inner Conductor	SPCW	
Dielectric	PTFE	
Shield	1. Tinned Copper	
Jacket	None	
Coax Diameter	0.02	
Minimum Bend Radius	0.05	
Length	6.0	
Operating Temperature	-55.0 to 85.0 °C	
RoHS Compliance	Yes	

**Drawing**



**Product Notes**