

# **P1CA-SAFPT-047CC-10**

SMA Female to Pigtail (no connector) cable assembly using 047CC Conformable Coax, 10 inches long, Operating to 6 GHz.

### **Product Features**

P1CA-SAFPT-047CC-10 is an RF Test Probe that is part of P1dB's semi-rigid, conformable, jacketed conformable and flexible Pigtail assembly series. It is a 10 inch SMA Female to a Pigtail Conformable cable assembly that utilizes 047CC conformable (no jacket) coax with a diameter of 0.047 inches. The Pigtail cable assembly operates to 6 GHz and is a popular solution for in-circuit RF probe testing.



## **Electrical Specification: T**<sub>Ambient</sub> = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		6.0	
Insertion Loss	DC to 1.0	dB/ft.			0.36	
	1.0 to 3.0	]			0.62	
	3.0 to 5.0	]			0.86	
Velocity Of Propagation		%		70.0		

## **Mechanical And Environmental Specifications:**

Parameter	Description	Notes
Connector 1	SMA Female	
Connector 1 Coupling Nut	None	
Connector 1 Body	Gold Plated Brass	
Connector 1 Contact	Gold Plated Beryllium Copper	
Connector 2	Pigtail - No Connector	
Coax Cable	Conformable	
Cable Type	047CC	
Cable Inner Conductor	SPCW	
Dielectric	PTFE	
Shield	1. Tinned Cu/Sn Braid	
Jacket	None	
Coax Diameter	0.047	
Minimum Bend Radius	0.125	
Length	10.0	
Operating Temprature	-55.0 to 125.0 °C	
RoHS Compliance	Yes	

### **Product Notes**