

## P1CA-SAFPT-085CJ-7

SMA Female to Pigtail (no connector) cable assembly using 085CJ Jacketed Conformable Coax, 7 inches long, Operating to 6 GHz.

#### **Product Features**

P1CA-SAFPT-085CJ-7 is an RF Test Probe that is part of P1dB's semi-rigid, conformable, jacketed conformable and flexible Pigtail assembly series. It is a 7 inch SMA Female to a Pigtail Jacketed Conformable cable assembly that utilizes 085CJ conformable coax with a diameter of 0.102 inches. The Pigtail cable assembly operates to 6 GHz and is a popular solution for in-circuit RF probe testing.



### **Electrical Specification:** T <sub>Ambient</sub> = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		6.0	
Insertion Loss	DC to 1.0	dB/ft.			0.22	
	1.0 to 3.0				0.49	
	3.0 to 5.0				0.83	
Velocity Of Propagation		%		70.0		

#### **Mechanical And Environmental Specifications:**

Parameter	Description	Notes
Connector 1	SMA Female	
Connector 1 Coupling Nut	None	
Connector 1 Body	Gold Plated Brass	
Connector 1 Contact	Gold Plated Beryllium Copper	
Connector 2	Pigtail - No Connector	
Coax Cable	Jacketed Conformable	
Cable Type	085CJ	
Cable Inner Conductor	SPCW	
Dielectric	PTFE	
Shield	1. Tinned Cu/Sn Braid	
Jacket	FEP	
Coax Diameter	0.102	
Minimum Bend Radius	0.125	
Length	7.0	
Operating Temprature	-55.0 to 200.0 °C	
RoHS Compliance	Yes	

#### **Drawing**



# P1CA-SAFPT-085CJ-7

SMA Female to Pigtail (no connector) cable assembly using 085CJ Jacketed Conformable Coax, 7 inches long, Operating to 6 GHz.



**Product Notes**