P1CA-SAFSAM-085SRSS-8

Cable Assembly, SMA Female to SMA Male, .085 Stainless Steel Semi-rigid Coax, 8 inch.
Frequency DC - 18 GHz.


Product Features

SMA female to SMA male semi rigid assembly, 8 inch,

Cable is stainless steel .085 inch.

Connectors are stainless steel.

Frequency is DC to 18 GHz.



Electrical Specification: $T_{Ambient}$ = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		18.0	

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	SMA Female	
Connector 2	SMA Male	
Coax Cable	Stainless Steel Semi Rigid	
Cable Type	.085 semi rigid	
Coax Diameter	0.085	
Length	length(in): length (in): 8.0	
RoHS Compliance	Yes	

Drawing

P1dB, Inc. 188 Martinvale Lane, San Jose, CA 95119 +1(408)613-4857

sales@p1dB.com

P1CA-SAFSAM-085SRSS-8

Cable Assembly, SMA Female to SMA Male, .085 Stainless Steel Semi-rigid Coax, 8 inch.
Frequency DC - 18 GHz.

DIMENSIONS	
Center Conductor Diameter	
(inch)	0.0201±0.0005
(mm)	0.51 ± 0.0127
Dielectric Diameter	
(inch)	0.0654±0.001
(mm)	1.66 ±0.0254
Outer Conductor Diameter	
(inch)	0.858±0.001
(mm)	2.16 ±0.0254
MATERIAL SPECIFICATIONS	
Outer Conductor	Stainless Steel
Dielectic	PTFE
Center Conductor	SPCW

Product Notes

P1dB, Inc. 188 Martinvale Lane, San Jose, CA 95119 +1(408)613-4857

sales@p1dB.com