P1CA-SAMRASAMRA-RG316-48

SMA Male Right Angle to SMA Male Right Angle, flex RG316 cable, 48 inch. Frequency DC to 6 GHz.

Product Features

SMA Male Right Angle to SMA Male Right Angle, flex RG316 cable, 48 inch.

Frequency DC to 6 GHz.



Electrical Specification: $T_{Ambient}$ = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		6.0	
VSWR	DC to 0.4	1:			1.2	
	0.4 to 1.0				1.25	
	1.0 to 2.4				1.3	
	2.4 to 0.5				1.35	
Insertion Loss	DC to 0.4	dB/ft.			0.18	
	0.4 to 1.0				0.31	
	1.0 to 2.4				0.49	
	2.4 to 0.5				0.67	
Velocity Of Propagation		%		69.5		

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	SMA Male Right Angle	
Connector 2	SMA Male Right Angle	
Length	48.0	
RoHS Compliance	Yes	


P1dB, Inc. 188 Martinvale Lane, San Jose, CA 95119 +1(408)613-4857

sales@p1dB.com

P1CA-SAMRASAMRA-RG316-48

SMA Male Right Angle to SMA Male Right Angle, flex RG316 cable, 48 inch. Frequency DC to 6 GHz.

Drawing



Product Notes

P1dB, Inc. 188 Martinvale Lane, San Jose, CA 95119 +1(408)613-4857

sales@p1dB.com