
P1CA-SAMSAM-081-150CM

Cable Assembly, SMA male to SMA male, 0.81mm flex, 150 cm. Frequency DC to 6 GHz.

Product Features

Cable Assembly, SMA male to SMA male, 0.81mm flex, 150 cm. Frequency DC to 6 GHz with a max VSWR 1.45.



Electrical Specification: T _{Ambient} = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		6.0	

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	SMA Male	
Connector 2	SMA Male	
RoHS Compliance	Yes	

Drawing

P1CA-SAMSAM-081-150CM

Cable Assembly, SMA male to SMA male, 0.81mm flex, 150 cm. Frequency DC to 6 GHz.



Construction and Specifications			
Description	Material	Diameter (inch)	
1. Inner Conductor	Silver Plated Copper Wire, 7 Strands	0.006	
2. Dielectric	fluorinated ethylene propylene (FEP)	0.016	
3. Braid	Tinned Copper Wire	-	
4. Jacket	FEP (Color: Black)	0.032	

Mechanical Specifications	
Max. Allowed Bend Radius: installation	0.35 inch

Environmental Specifications	
Operating Temperature Range	-40 °C to +90 °C

Electrical Specifications			
Max. operating frequency	6 GHz		
Velocity of Propagation	69%		
Impedance	50 ohms		

Product Notes