# P1CA-SAMSAM-085CC-24

SMA Male to SMA Male cable assembly using 085CC Conformable Coax, 24 inches long, Operating to 26.5 GHz.

#### **Product Features**

P1CA-SAMSAM-085CC-24 is an RF Cable that is part of P1dB's YouForm<sup>™</sup> conformable cable assembly series. It is a 24 inch SMA Male to SMA Male Conformable cable assembly that utilizes 085CC conformable coax with a diameter of 0.085 inches. The RF cable assembly operates to 26.5 GHz with a max VSWR of 1.35:1. YouForm<sup>™</sup> cables are conformable and jacketed conformable versions 085 and 141 semi-rigid coax cables and meet RG402 and RG405 dimensional and electrical specifications. YouForm<sup>™</sup> cable assemblies can operate up to 26.5 GHz, depending on the configuration. The advantage of YouForm<sup>™</sup> conformable cables over semi-rigid are their ability to be formed by hand multiple times, while semi-rigid cables can be formed only once with special bending tools.



Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		26.5	
VSWR	DC to 1.0	1:			1.25	
	1.0 to 5.0				1.3	
	5.0 to 10.0				1.32	
	10.0 to 26.5				1.35	
Insertion Loss	DC to 1.0	dB/ft.			0.22	
	1.0 to 5.0				0.49	
	5.0 to 10.0				0.83	
	10.0 to 26.5				1.18	
Velocity Of Propagation		%		70.0		

## Electrical Specification: T <sub>Ambient</sub> = 25° C

### **Mechanical And Environmental Specifications:**

Parameter	Description	Notes
Connector 1	SMA Male	
Connector 1 Coupling Nut	Passivated Stainless Steel	
Connector 1 Body	Gold Plated Brass	

188 Martinvale Lane, San Jose, CA 95119

# P1CA-SAMSAM-085CC-24

SMA Male to SMA Male cable assembly using 085CC Conformable Coax, 24 inches long, Operating to 26.5 GHz.

Parameter	Description	Notes
Connector 1 Contact	Gold Plated Brass	
Connector 2	SMA Male	
Connector 2 Coupling Nut	Passivated Stainless Steel	
Connector 2 Body	Gold Plated Brass	
Connector 2 Contact	Gold Plated Brass	
Coax Cable	Conformable	
Cable Type	085CC	
Cable Inner Conductor	SPCW	
Dielectric	PTFE	
Shield	1. Tinned Cu/Sn Braid	
Jacket	FEP	
Coax Diameter	0.085	
Minimum Bend Radius	0.38	
Length	24.0	
RoHS Compliance	Yes	

### Drawing



#### **Product Notes**