

Product Features

P1CA-SAMSAM-085CC-48 is an RF Cable that is part of P1dB's YouForm™ conformable cable assembly series. It is a 48 inch SMA Male to SMA Male Conformable cable assembly that utilizes 085CC conformable coax with a diameter of 0.085 inches. The RF cable assembly operates to 26.5 GHz with a max VSWR of 1.35:1.

YouForm™ cables are conformable and jacketed conformable versions 085 and 141 semi-rigid coax cables and meet RG402 and RG405 dimensional and electrical specifications. YouForm™ cable assemblies can operate up to 18 GHz, depending on the configuration. The advantage of YouForm™ conformable cables over semi-rigid are their ability to be formed by hand multiple times, while semi-rigid cables can be formed only once with special bending tools.



Electrical Specification: T_{Ambient} = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		26.5	
VSWR	DC to 1.0	1:			1.25	
	1.0 to 5.0				1.3	
	5.0 to 10.0				1.32	
	10.0 to 26.0				1.35	
Insertion Loss	DC to 1.0	dB/ft.			0.22	
	1.0 to 5.0				0.49	
	5.0 to 10.0				0.83	
	10.0 to 26.0				1.18	
Velocity Of Propagation		%		70.0		

Mechanical And Environmental Specifications:


Parameter	Description	Notes
Connector 1	SMA Male	
Connector 1 Coupling Nut	Passivated Stainless Steel	
Connector 1 Body	Gold Plated Brass	
Connector 1 Contact	Gold Plated Brass	
Connector 2	SMA Male	
Connector 2 Coupling Nut	Passivated Stainless Steel	
Connector 2 Body	Gold Plated Brass	
Connector 2 Contact	Gold Plated Brass	
Coax Cable	Conformable	
Cable Type	085CC	
Cable Inner Conductor	SPCW	
Dielectric	PTFE	
Shield	1. Tinned Cu/Sn Braid	

P1CA-SAMSAM-085CC-48

SMA Male to SMA Male cable assembly using 085CC Conformable Coax, 48 inch, frequency to 26.5 GHz.

Parameter	Description	Notes
Jacket	FEP	
Coax Diameter	0.085	
Minimum Bend Radius	0.38	
Length	48.0	
Operating Temperature	-85.0 to 165 °C	
RoHS Compliance	Yes	

Drawing



Product Notes