

RF flexible cable assembly, SMA Male to SMA Male, 0.190 inch flexible coaxial cable, 240 inch (20 ft). Length +/- 1 inch. Low loss phase stable test cables. Frequency DC to 18 GHz.

Product Features

P1CA-SAMSAM-F190-240 is a low loss, phase stable test cables with SMA male connectors.
The cable is F190 triple shield flex which is 0.19 inch diameter.
Frequency is DC to 18 GHz.



Electrical Specification: $T_{\text{Ambient}} = 25^{\circ}\text{C}$



Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		18.0	

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	SMA Male	
Connector 2	SMA Male	
Length	240.0	
RoHS Compliance	Yes	

Drawing


RF flexible cable assembly, SMA Male to SMA Male, 0.190 inch flexible coaxial cable, 240 inch (20 ft). Length +/- 1 inch. Low loss phase stable test cables. Frequency DC to 18 GHz.



Attenuation (Typical @25°C&VSWR=1.0) &Power (VSWR=1.0;40°C;Sea Level)

Frequency MHz	300	1000	2000	4000	6000	8000	10000	12000	13500	14000	16000	18000
dB/100 m	21.0	40.0	58.9	87.9	112.0	133.6	153.5	172.3	185.8	190.2	207.4	224.0
Avg.Power kW	1.822	0.954	0.648	0.434	0.341	0.286	0.249	0.222	0.206	0.201	0.184	0.170
K1=	1.1414400					K2=	0.0039360					

Calculate Attenuation= $K1 \cdot \sqrt{FMHz} + K2 \cdot FMHz$



Product Notes

Temp range -55 to +125 deg C