

P1CA-SAMSAM-RG316-40

SMA Male to SMA Male cable using RG-316 RG Type Flex Coax, 40 inch. Frequency DC to 6 GHz.

Product Features



Electrical Specification: $T_{\text{Ambient}} = 25^{\circ}\text{C}$

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		6.0	
VSWR	DC to 0.4	1:			1.2	
	0.4 to 1.0				1.25	
	1.0 to 2.4				1.3	
	2.4 to 0.5				1.35	
Insertion Loss	DC to 0.4	dB/ft.			0.18	
	0.4 to 1.0				0.31	
	1.0 to 2.4				0.49	
	2.4 to 0.5				0.67	
Velocity Of Propagation		%		69.5		

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	SMA Male	
Connector 1 Coupling Nut	Gold Plated Brass	
Connector 1 Body	Gold Plated Brass	
Connector 1 Contact	Gold Plated Brass	
Connector 2	SMA Male	

P1CA-SAMSAM-RG316-40

SMA Male to SMA Male cable using RG-316 RG Type Flex Coax, 40 inch. Frequency DC to 6 GHz.



Parameter	Description	Notes
Connector 2 Coupling Nut	Gold Plated Brass	
Connector 2 Body	Gold Plated Brass	
Connector 2 Contact	Gold Plated Brass	
Coax Cable	RG Type Flex	
Cable Type	RG-316	
Cable Inner Conductor	77.0067 SPCW	
Dielectric	PTFE	
Jacket	FEP	
Coax Diameter	0.098	
Minimum Bend Radius	0.5	
Length	40.0	
RoHS Compliance	Yes	

Product Notes