


P1CA-SAMSAM-SS141-1M-PM

RF cable assembly, SMA Male to SMA Male, SS141 flexible coaxial cable, 1 meter.

Supplied as a phase matched pair (2 cables). Price is per cable, minimum order 2 cables. Phase matched +/- 5 degrees at 10 GHz, operating to 18 GHz. Contact P1dB for matched sets > quantity 2.

Product Features

P1dB's P1CA-SAMSAM-SS141-1M-PM is a 50 Ohm RF cable assembly, supplied as TBD # of phase matched cables. It is an SMA male to SMA male cable using P1dB's SS141 flex coax which is a phase stable RF cable with 0.160 inch (4mm) outer diameter. The cable is 1 meter long and the cables are phase matched to 5 degrees measured at 10 GHz. Operating to 18 GHz, the P1CA-SAMSAM-SS141-1M-PM is a low loss flex cable with a minimum bend radius of 0.8 inches. Maximum VSWR to 18 GHz is 1.25.



Electrical Specification: $T_{\text{Ambient}} = 25^{\circ}\text{C}$

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		18.0	
VSWR	DC to 1.0	1:			1.1	
	1.0 to 10.0				1.2	
	10.0 to 18.0				1.25	
Insertion Loss	DC to 1.0	dB/ft.			0.15	
	1.0 to 10.0				0.45	
	10.0 to 18.0				0.64	
Velocity Of Propagation		%		70.0		

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	SMA Male	
Connector 1 Coupling Nut	Passivated Stainless Steel	
Connector 1 Body	Passivated Stainless Steel	
Connector 1 Contact	Gold Plated Brass	
Connector 2	SMA Male	
Connector 2 Coupling Nut	Passivated Stainless Steel	
Connector 2 Body	Passivated Stainless Steel	

P1CA-SAMSAM-SS141-1M-PM

RF cable assembly, SMA Male to SMA Male, SS141 flexible coaxial cable, 1 meter.

Supplied as a phase matched pair (2 cables). Price is per cable, minimum order 2 cables. Phase matched +/- 5 degrees at 10 GHz, operating to 18 GHz. Contact P1dB for matched sets > quantity 2.


Parameter	Description	Notes
Connector 2 Contact	Gold Plated Brass	
Coax Cable	High Performance	
Cable Type	SS141	
Cable Inner Conductor	SPC	
Dielectric	PTFE	
Shield	1. SPC Braid, SPC Ribbon	
Jacket	FEP	
Coax Diameter	0.163	
Minimum Bend Radius	0.8	
Operating Temperature	-55.0 to 125.0 °C	
RoHS Compliance	Yes	

Graph

P1CA-SAMSAM-SS141-1M-PM

RF cable assembly, SMA Male to SMA Male, SS141 flexible coaxial cable, 1 meter.

Supplied as a phase matched pair (2 cables). Price is per cable, minimum order 2 cables. Phase matched +/- 5 degrees at 10 GHz, operating to 18 GHz. Contact P1dB for matched sets > quantity 2.



P1CA-SAMSAM-SS141-1M-PM

RF cable assembly, SMA Male to SMA Male, SS141 flexible coaxial cable, 1 meter.

Supplied as a phase matched pair (2 cables). Price is per cable, minimum order 2 cables. Phase matched +/- 5 degrees at 10 GHz, operating to 18 GHz. Contact P1dB for matched sets > quantity 2.

Product Notes