


# P1CA-STMSTM-ST085-6

SMA Male to SMA Male cable assembly using ST085 Tight-Flex, Triple Shielded Coax, 6 inches long, Operating to 18 GHz.

## Product Features

P1CA-STMSTM-ST085-6 is an RF Cable that is part of P1dB's Tight-Flex™ cable assembly series. With a minimum bend radius of 0.2 inch, the cable allows bends at the connector end eliminating the need for a right angle connector. This assembly is a 6 inch SMA Male to SMA Male cable assembly that utilizes ST085 Tight-Flex, Triple Shielded coax, which is 0.104 inches in diameter. The Tight-Flex™ cable assembly operates to 18 GHz with a max VSWR of 1.30:1.

Tight-Flex™ cable assemblies are a flexible version of RG405 semi-rigid and 085 conformable coax cables that meet RG405 dimensional and electrical specifications. Tight-Flex™ cable assemblies can operate up to 40 GHz, depending on the installed connectors. The advantage of Tight-Flex™ cables over other 085 flex cables are their triple shielding that add additional RF stability even during tight bends.



## Electrical Specification: T<sub>Ambient</sub> = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		18.0	
VSWR	DC to 1.0	1:			1.15	
	1.0 to 5.0				1.2	
	5.0 to 10.0				1.25	
	10.0 to 18.0				1.3	
Insertion Loss	DC to 1.0	dB/ft.			0.21	
	1.0 to 5.0				0.51	
	5.0 to 10.0				0.75	
	10.0 to 18.0				1.04	
Velocity Of Propagation		%		70.0		

## Mechanical And Environmental Specifications:


Parameter	Description	Notes
Connector 1	SMA Male	

# P1CA-STMSTM-ST085-6

SMA Male to SMA Male cable assembly using ST085 Tight-Flex, Triple Shielded Coax, 6 inches long, Operating to 18 GHz.

Parameter	Description	Notes
Connector 1 Coupling Nut	Passivated Stainless Steel	
Connector 1 Body	Passivated Stainless Steel	
Connector 1 Contact	Gold Plated Brass	
Connector 2	SMA Male	
Connector 2 Coupling Nut	Passivated Stainless Steel	
Connector 2 Body	Passivated Stainless Steel	
Connector 2 Contact	Gold Plated Brass	
Coax Cable	Tight-Flex, Triple Shielded	
Cable Type	ST085	
Cable Inner Conductor	SPCW	
Dielectric	PTFE	
Shield	1. SPC Tape, Aluminum Tape, SPC Braid	
Jacket	FEP	
Coax Diameter	0.104	
Minimum Bend Radius	0.2	
Length	6.0	
RoHS Compliance	Yes	


## Drawing



## Graph

# P1CA-STMSTM-ST085-6

SMA Male to SMA Male cable assembly using ST085 Tight-Flex, Triple Shielded Coax, 6 inches long, Operating to 18 GHz.



# P1CA-STMSTM-ST085-6

SMA Male to SMA Male cable assembly using ST085 Tight-Flex, Triple Shielded Coax, 6 inches long, Operating to 18 GHz.

DIMENSIONS			
Center Conductor Diameter			
(inch)		0.0201	
(mm)		0.51	
Dielectric Diameter			
(inch)		0.0641	
(mm)		1.63	
Diameter Over Inner Foil			
(inch)		0.0708	
(mm)		1.80	
Diameter Over Outer Foil			
(inch)		0.0748	
(mm)		1.90	
Diameter over Braid			
(inch)		0.0885	
(mm)		2.25	
Jacket Diameter			
(inch)		0.104	
(mm)		2.64	
MATERIAL SPECIFICATIONS			
Jacket		FEP(BLUE)	
Braid		Round Silver Plated Copper	
Outer Foil		Aluminium Tape	
Inner Foil		Silver Plated Copper Tape	
Dielectric		Solid PTFE	
Center Conductor		Solid SPCW	
ELECTRICAL CHARACTERISTICS			
Impedance		50±2	
Capacitance (Nominal)			
(pF/ft)		29.4	
(pF/m)		96.4	
Velocity of Propagation (%)		70	
Cutt Off Frequency (GHz)		63	
Shielding Effectiveness		> -110dB	
Max. Attenuation Max Power (Watts)	Attenuation		Power
	dB/100Ft	dB/100M	
400MHz	14	45.9	240
1GHz	23	75.4	160
3GHz	39	128	80
5GHz	52	170.6	57
10GHz	80	262.4	44
18GHz	110	361	33
25GHz	131	430	29
30GHz	146	479	26
35GHz	160	525	23
40GHz	173	567	22
45GHz	183	600	20
50GHz	195	640	18

## Product Notes

Temp range: -55 to +125 deg C

Minimum bend radius: 0.2 inch (5.1 mm)

P1dB, Inc.

188 Martinvale Lane, San Jose, CA 95119

+1(408)613-4857

sales@p1dB.com