


P1CA-STMTMF-ST085-24

SMA Male to SMPM Female cable assembly using ST085 Tight-Flex, Triple Shielded Coax, 24 inches long, Operating to 18 GHz.

Product Features



Electrical Specification: $T_{\text{Ambient}} = 25^{\circ}\text{C}$

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		18.0	
VSWR	DC to 1.0	1:			1.15	
	1.0 to 5.0				1.2	
	5.0 to 10.0				1.25	
	10.0 to 18.0				1.35	
Insertion Loss	DC to 1.0	dB/ft.			0.21	
	1.0 to 5.0				0.51	
	5.0 to 10.0				0.75	
	10.0 to 18.0				1.04	
Velocity Of Propagation		%		70.0		

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	SMA Male	
Connector 1 Coupling Nut	Passivated Stainless Steel	
Connector 1 Body	Passivated Stainless Steel	
Connector 1 Contact	Gold Plated Brass	
Connector 2	SMPM Female	


P1CA-STMTMF-ST085-24

SMA Male to SMPM Female cable assembly using ST085 Tight-Flex, Triple Shielded Coax, 24 inches long, Operating to 18 GHz.



Parameter	Description	Notes
Connector 2 Coupling Nut	None	
Connector 2 Body	Gold Plated Beryllium Copper	
Connector 2 Contact	Gold Plated Beryllium Copper	
Coax Cable	Tight-Flex, Triple Shielded	
Cable Type	ST085	
Cable Inner Conductor	SPCW	
Dielectric	PTFE	
Shield	1. SPC Tape, Aluminum Tape, SPC Braid	
Jacket	FEP	
Coax Diameter	0.104	
Minimum Bend Radius	0.2	
Length	24.0	
Operating Temperature	-55.0 to 200.0 °C	
RoHS Compliance	Yes	


Drawing



Graph

P1CA-STMTMF-ST085-24

SMA Male to SMPM Female cable assembly using ST085 Tight-Flex, Triple Shielded Coax, 24 inches long, Operating to 18 GHz.



Product Notes