

Product Features

P1CA-STMTPF-ST085-5 is an RF Cable that is part of P1dB's Tight-Flex™ cable assembly series. It is a 5 inch SMA Male to SMP Female cable assembly that utilizes ST085 Tight-Flex, Triple Shielded coax, which is 0.104 inches in diameter. This Tight-Flex™ cable assembly operates to 18 GHz with a max VSWR of 1.35.

Tight-Flex™ cable assemblies are a flexible version of RG405 semi-rigid and 085 conformable coax cables that meet RG405 dimensional and electrical specifications. Tight-Flex™ cable assemblies can operate up to 40 GHz, depending on the installed connectors. The advantage of Tight-Flex™ cables over other 085 flex cables are their triple shielding that add additional RF stability even during tight bends.



Electrical Specification: T_{Ambient} = 25° C


Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		18.0	
VSWR	DC to 1.0	1:			1.15	
	1.0 to 5.0				1.2	
	5.0 to 10.0				1.25	
	10.0 to 18.0				1.35	
Insertion Loss	DC to 1.0	dB/ft.			0.21	
	1.0 to 5.0				0.51	
	5.0 to 10.0				0.75	
	10.0 to 18.0				1.04	
Velocity Of Propagation		%		70.0		

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	SMA Male	
Connector 1 Coupling Nut	Passivated Stainless Steel	
Connector 1 Body	Passivated Stainless Steel	
Connector 1 Contact	Gold Plated Brass	
Connector 2	SMP Male	
Connector 2 Coupling Nut	None	
Connector 2 Body	Gold Plated Beryllium Copper	
Connector 2 Contact	Gold Plated Beryllium Copper	
Coax Cable	Tight-Flex, Triple Shielded	
Cable Type	ST085	
Cable Inner Conductor	SPCW	
Dielectric	PTFE	
Shield	1. SPC Tape, Aluminum Tape, SPC Braid	
Jacket	FEP	
Coax Diameter	0.104	

Parameter	Description	Notes
Minimum Bend Radius	0.2	
Length	5.0	
Operating Temperature	-55.0 to 125.0 °C	
RoHS Compliance	Yes	

Drawing



Graph

DIMENSIONS			
Center Conductor Diameter			
(inch)		0.0201	
(mm)		0.51	
Dielectric Diameter			
(inch)		0.0641	
(mm)		1.63	
Diameter Over Inner Foil			
(inch)		0.0708	
(mm)		1.80	
Diameter Over Outer Foil			
(inch)		0.0748	
(mm)		1.90	
Diameter over Braid			
(inch)		0.0885	
(mm)		2.25	
Jacket Diameter			
(inch)		0.104	
(mm)		2.64	
MATERIAL SPECIFICATIONS			
Jacket		FEP(BLUE)	
Braid		Round Silver Plated Copper	
Outer Foil		Aluminium Tape	
Inner Foil		Silver Plated Copper Tape	
Dielectric		Solid PTFE	
Center Conductor		Solid SPCW	
ELECTRICAL CHARACTERISTICS			
Impedance		50±2	
Capacitance (Nominal)			
(pF/ft)		29.4	
(pF/m)		96.4	
Velocity of Propagation (%)		70	
Cutt Off Frequency (GHz)		63	
Shielding Effectiveness		> -110dB	
Max. Attenuation		Attenuation	
Max Power (Watts)		dB/100Ft	Power
			dB/100M
400MHz		14	45.9
1GHz		23	75.4
3GHz		39	128
5GHz		52	170.6
10GHz		80	262.4
18GHz		110	361

Product Notes