P1CO-SAF4-F015-27G

Connector, SMA Female, 4-Hole Panel Mount, Field Replaceable, Socket for .015 Pin, 27 GHz

Product Features

P1CO-SAF4-F015-27G is a 50 Ohm RF connector, SMA field replaceable, 4 hole flange mount that mates with a .015 inch pin.

Operating to 27 Ghz with a maximum VSWR of 1.20, the P1CO-SAF4-F015-27G features a passivated stainless steel body and includes an EMI gasket to reduce RF leakage.




Electrical Specification: $T_{Ambient}$ = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		27.0	
Impedance				50.0		

Mechanical And Environmental Specifications:

Parameter	Description	Notes
RoHS Compliance	Yes	

Drawing



P1dB, Inc. 188 Martinvale Lane, San Jose, CA 95119 +1(408)613-4857

sales@p1dB.com

P1CO-SAF4-F015-27G

Connector, SMA Female, 4-Hole Panel Mount, Field Replaceable, Socket for .015 Pin, 27 GHz

Graph

Parts	Material	Plating (Micro-inch)
EMI Gasket	Conductive Slicon Elastomers	
Contact Pin	Beryllium Copper	Gold 20 Over Nickel 50 Over Copper 50
Insulator	Teflon	
Body	Stainless	Passivated

Product Notes

P1dB, Inc. 188 Martinvale Lane, San Jose, CA 95119 +1(408)613-4857

sales@p1dB.com